



REPEAT WEFT REPETICIÓN TRAMA:  
REPEAT WARP REPETICIÓN URDIMBRE:

## GEODARK FR 18

### GEODARK FR 3.10 ULTRADARK 18



## TECHNICAL SHEET / CARACTERÍSTICAS TÉCNICAS

|                                                                                |                 |                    |
|--------------------------------------------------------------------------------|-----------------|--------------------|
| WIDTH (inches) / ANCHO (cm)                                                    | 122 / 310       |                    |
| HS CODE / PARTIDA ARANCELARIA                                                  | 54075300        |                    |
| ROLL LENGTH (yd) / TAMAÑO PIEZA (mts)                                          | 33.0 / 30       |                    |
| COMPOSITION / COMPOSICION                                                      | PES100%         |                    |
| WEIGHT (oz/yd2) / PESO (gr/m2) (+/-5%)                                         | 15.01 / 510     |                    |
| WEIGHT (oz/yd) / PESO (gr/ml)                                                  | 50.99 / 1581.00 |                    |
| COLOUR FASTNESS TO LIGHT ( degrees ) (1-8) / SOLIDEZ A LA LUZ ( grados ) (1-8) | 5               | UNE EN ISO 105-B02 |
| COLOUR FASTNESS TO WASH ( degrees ) (1-5) / SOLIDEZ AL LAVADO ( grados )       | 5               | UNE EN ISO 105-C06 |
| (%) WARP SHRINKAGE / ENCOGIMIENTO URDIMBRE ( % )                               | 1.8             | UNE EN ISO 5077.   |
| (%) WEFT SHRINKAGE / ENCOGIMIENTO TRAMA ( % )                                  | 0.5             | UNE EN ISO 5077    |
| WARP SEAM SLIPPAGE (mm) / DESLIZAMIENTO DE LA COSTURA URDIMBRE (mm)            | 2.5             | UNE EN ISO 13936-1 |
| WEFT SEAM SLIPPAGE (mm) / DESLIZAMIENTO DE LA COSTURA TRAMA ( mm )             | 3.6             | UNE EN ISO 13936-1 |
| FIRE RETARDANT RULE / IGNÍFUGOS UNE EN 13773:2003                              | C-1             | UNE EN 13773:2003  |
| OPACITY 100000 LUX / OPACIDAD 100000 LUX                                       | 0-0.25          | CS1451LUX          |