




VITA 04

VITA 3.10 VISILLO IGNIFU COL04



REPEAT WEFT REPETICIÓN TRAMA:
REPEAT WARP REPETICIÓN URDIMBRE:

TECHNICAL SHEET / CARACTERÍSTICAS TÉCNICAS

WIDTH (inches) / ANCHO (cm)	122 / 310	
HS CODE / PARTIDA ARANCELARIA	55121990	
ROLL LENGTH (yd) / TAMAÑO PIEZA (mts)	33.0 / 30	
COMPOSITION / COMPOSICION	PES 100%	
WEIGHT (oz/yd ²) / PESO (gr/m ²) (+/-5%)	3.97 / 135	
WEIGHT (oz/yd) / PESO (gr/ml)	13.50 / 418.50	
COLOUR FASTNESS TO LIGHT (degrees) (1-8) / SOLIDEZ A LA LUZ (grados) (1-8)	5	UNE EN ISO 105-B02
COLOUR FASTNESS TO WASH (degrees) (1-5) / SOLIDEZ AL LAVADO (grados)	5	UNE EN ISO 105-C06
(%) WARP SHRINKAGE / ENCOGIMIENTO URDIMBRE (%)	0.8	UNE EN ISO 5077.
(%) WEFT SHRINKAGE / ENCOGIMIENTO TRAMA (%)	0.6	UNE EN ISO 5077
FIRE RETARDANT RULE / IGNÍFUGOS UNE EN 13773:2003	C1	UNE EN 13773:2003
FIRE RETARDAN RULE / IGNIFUGOS BS 5867-2	PASA	BS 5867-2